

# Gas Sensor ME 1250

## Chloroform CHCl<sub>3</sub>



# CHCl<sub>3</sub>

<b>Gas</b>	Chloroform
<b>Formula</b>	CHCl <sub>3</sub>
<b>CAS number</b>	67-66-3
<b>Max. workplace concentration</b>	0.5 ppm
<b>Relative density</b>	4.12 ▼
<b>Appearance</b>	Colorless Sweet odor
<b>Hazards</b>	Toxic Narcotic

- **Automatic zero point calibration**
- **Active noise reduction on the output signal**
- **Linear measurement signal depending on the gas concentration**
- **High response sensitivity with a short response time**
- **Selective and reliable measurement with stable measuring signal and zero point**
- **Temperature compensated measurement**
- **Long service life**


The ME1250 Gas Sensor is a remote measuring unit for monitoring gas concentration of chloroform. The sensor is used as a leak detector for personal protection and to protect against the anesthetic effect of the gas.

The microprocessor-controlled electronics of the sensor, adapted to the specific properties of the measuring cell, enable fast and reliable signal processing. The measured gas concentration is transmitted to a Gas Control Panel, which can manage a large number of distributed gas sensors.



Thanks to bus communication, only one cable is required, which can be continued from sensor to sensor. The ME 1250 Gas Sensor is also available with an analogue output signal of 4...20 mA. The measured gas concentration can thereby be processed by other PLC (Programmable Logic Controllers).

The optional relay module expands the ME 1250 Gas Sensor internally with 3 relays for direct switching of signal transmitters without the use of a control panel.

## ■ Technical Specifications

Measurement method	Semiconductor / Chemosorption	
Measuring range	0...20 ppm	other measuring ranges on request
Alarm thresholds	Alarm 1: 10 ppm Alarm 2: 16 ppm	recommendation
Lifespan in air	up to 3 years	according to cell manufacturer
Break-in period	24 h	according to cell manufacturer
Response time $t_{80}$	< 60 sec	
Operating voltage	10...28 VDC	nominal 24 VDC
Ambient temperature	-20...+40 °C	
Humidity	15...90% rF	non-condensing
Mounting height	30 cm above floor	heavier than air ▼
Casing	<i>Default:</i> Powder-coated aluminum Orange RAL 2004 80 x 125 x 59 mm 500 g	<i>Optional:</i> ABS plastic Light gray RAL 7035 81 x 121 x 56 mm 250 g
Cable entry	M20	
EU conformity	CE mark including EMC test	

## ■ Versions

Article code	<b>12BUS-CHCL3-21</b>	<b>1250-CHCL3-21</b>
Description	ME 1250 Bus	ME 1250 Analogue
Output signal	Bus communication with Control Panel	Analogue 4...20 mA Load max. 800 Ω at 24 V input
Connection	4-core cable U72M 1x4x0.6 mm Shielded	3-core cable U72M 1x4x0.6 mm or CY 0.5 mm <sup>2</sup> Shielded
		
Topology	Bus, tree or star topology	Star topology
Power	< 1.9 W	< 2.5 W

## ■ Cross sensitivity

Due to the measuring method, all hydrocarbon compounds are detected. If different gases are to be expected, calibration should be made to the substance for which the sensor has the lowest sensitivity.

## ■ Accessories

Article code	
<b>1250-REL</b>	Relay module for single sensor
<b>1250-AIR-BOX</b>	Add-on box for ventilation duct
<b>1250-AIR-FLOW</b>	Hose fitting
<b>1250-SUP</b>	Mounting plate for round columns
<b>1250-SCHUTZ</b>	Weather protection

## ■ Maintenance

Annual calibration and function check with calibration gas, carried out by trained staff.

## ■ Consumables

Article code	
<b>CELL-HAL-832</b>	Measuring cell for refrigerant/chloroform Lifespan: up to 3 years

- The measuring cell can react to larger fluctuations in humidity