



C₄H₁₀

Gas	n-Butane
Refrigerant	R-600
Formula	C ₄ H ₁₀
CAS number	106-97-8
Lower Explosive Limit (LEL)	1.4 Vol.-%
Relative density	2.80 ▼
Appearance	Colorless Odorless
Hazards	Highly flammable Suffocating, narcotic

- Automatic zero point calibration
- Active noise reduction on the output signal
- Linear measurement signal depending on the gas concentration
- High response sensitivity with a short response time
- Selective and reliable measurement with stable measuring signal and zero point
- Temperature compensated measurement
- Insensitive to other gases
- Insensitive to room temperature and humidity
- No destruction of the measuring cell at high gas concentrations
- Very long service life due to the optical measuring method



The ME1250 Gas Sensor is a remote measuring unit for monitoring gas concentration and is used as a leak detector or for explosion protection.

The microprocessor-controlled electronics of the sensor, adapted to the specific properties of the measuring cell, enable fast and reliable signal processing. The measured gas concentration is transmitted to a Gas Control Panel, which can manage a large number of distributed gas sensors.



Thanks to bus communication, only one cable is required, which can be continued from sensor to sensor. The ME 1250 Gas Sensor is also available with an analogue output signal of 4...20 mA. The measured gas concentration can thereby be processed by other PLC (Programmable Logic Controllers).

The optional relay module expands the ME 1250 Gas Sensor internally with 3 relays for direct switching of signal transmitters without the use of a control panel.

■ Technical Specifications

Measurement method	Infrared / Optical	
Measuring range	0...100% LEL	other measuring ranges on request
Alarm thresholds	Alarm 1: 20% LEL Alarm 2: 40% LEL	recommendation
Lifespan in air	10 years	according to cell manufacturer
Break-in period	3 min	according to cell manufacturer
Response time t_{90}	10 sec	
Operating voltage	10...28 VDC	nominal 24 VDC
Ambient temperature	-40...+60 °C	
Humidity	20...98% rF	non-condensing
Mounting height	30 cm above floor	heavier than air 
Casing	<i>Default:</i> Powder-coated aluminum Orange RAL 2004 80 x 125 x 59 mm 500 g	<i>Optional:</i> ABS plastic Light gray RAL 7035 81 x 121 x 56 mm 250 g
Cable entry	M20	
EU conformity	CE mark including EMC test	

■ Versions

Article code	12IRB-R600-12	12IR-R600-12
Description	ME 1250 Bus	ME 1250 Analogue
Output signal	Bus communication with Control Panel	Analogue 4...20 mA Load max. 800 Ω at 24V input
Connection	4-core cable U72M 1x4x0.6 mm Shielded	3-core cable U72M 1x4x0.6 mm or CY 0.5 mm ² Shielded
		
Topology	Bus, tree or star topology	Star topology
Power	< 1.2 W	< 1.8 W

■ Cross sensitivity

Due to the optical measuring method, the measurement is very selective.

■ Accessories

Article code	1250-REL	Relay module for single sensor
	1250-AIR-BOX	Add-on box for ventilation duct
	1250-AIR-FLOW	Hose fitting
	1250-SUP	Mounting plate for round columns
	1250-SCHUTZ	Weather protection

■ Maintenance

Annual calibration and function check with calibration gas, carried out by trained staff.

■ Consumables

No wearing parts.

■ Related Products

Article code	12IRB-R600A-12	Gas Sensor ME 1250 Bus Isobutane R-600A
	12IR-R600A-12	Gas Sensor ME 1250 Analogue Isobutane R-600A